



TESTCERTIFIKAT FOR PUMPE PUMP TEST SHEET

SPX Flow Technology Poland Sp. Z o.o.
ul. Hermana Frankego 9
85-862 Bydgoszcz
Telephone +48 52 5259 900
www.spxft.com

LEVERINGSADRESSE / PLACE OF DELIVERY
SPX FLOW TECHNOLOGY AUSTRALIA PTY
300 WELLINGTON RD
MULGRAVE VIC 3170
AUSTRALIA

VORT ORDRE NR. OUR ORDER NO.	DERES ORDRE YOUR ORDER	KUNDE NR. CUSTOMER NO.	SERIENUMMER SERIAL NUMBER.
02280894	4501749294	C5035	10009530

PUMPETYP OG BESKRIVELSE / PUMP TYPE AND DESCRIPTION

DW4/073/10S/C-B		SHAFT VIEWED	SHAFT VIEWED FROM FRONT COVER
IN/OUTLET POSITION	VERTICAL	LABELS	APV LABEL
SURFACEFINISH	STANDARD 3A	MACHINERY DIRECTIVE	CE DECLARATION OF CONFORMITY
SPECIAL DOCUMENTATION	NONE	ATEX DIRECTIVE	NO
PUMPSIZE	4/073/10	MANUAL LANGUAGE	ENGLISH
THERMAL JACKET	NO		
ROTOR CASE	RECTANGULAR INLET		
RELIEF VALVE (PRV)	NO		
MATERIAL FOR GASKETS	VITON		
SHAFT SEAL	SIC/CAR SINGLE MECH.		
OIL SEAL MATERIAL	VITON		
ROTOR	316L HIGH TEMPERATURE 180C		
TYPE OF FITTING, OUTLET	BS4825 part 5 RJT MALE PART		
SIZE OF OUTLET FITTING	3" / Ø76		
BARESHAF/UNIT	BARESHAF		
SHAFT/INLET POSITION	SHAFT LEFT; INLET BOTTOM		

TESTRESULTAT / TEST RESULT

Performance test

Test liquid: Water
Temp.: 20°C

Test Condition Variables (TCV)		Test result Variables (TRV)	
Speed [rpm]	Diff.pres [bar]	Flow [L/min]	Torque [Nm]
1200	10	608	135
1200	10	609	137
+/- 1%	+/- 4%	+ ∞ /- 0	+ 0 /- ∞

Hydrostatic test

Pressure:
[bar]

Observation:

Observed values:

Clockwise
Anti clockwise
Acceptance limits:

1200	10	608	135
1200	10	609	137
+/- 1%	+/- 4%	+ ∞ /- 0	+ 0 /- ∞

Relief valve test:

Required value:	Observed value:
[bar]	

BEMÆRKNINGER NOTES	TEST DATO TEST DATE	OPERATØR OPERATOR	ACCEPT ACCEPTANCE
	01.02.2017	R.K	R.K